
HUBBELL
Premise Wiring

PROClick Connector, SC, OS2, Blue, 12 Pack



By Hubbell Premise Wiring
Catalog # FCSC900KSM12

Fiber Optic Connectors, ProClick SC, Singlemode Pre-Polished, 10GHz 900, 12Pack

Features

- Terminate in Less than 60 Seconds
- RoHS Compliant and Bulk Packed in Recyclable Cartons

Application

Interconnect

Performance

Optical - Insertion loss - 0.5dB (0.35dB typical), 0.75dB max, Optical - Mating durability - 500 cycles <, 0.1dB change, Optical - Multimode return loss - 35dB Typ, 22dB minimum, Optical - Singlemode return loss - 55dB Typ, 40dB minimum, Environmental - Operating temperature - 0 ºC to +70 ºC

Specifications

Environmental Conditions	Indoor
Industry Standard(s)	• Telcordia GR-326-CORE • TIA-568-C.3 • TIA-604-FOCIS

Conductor

Fiber Size	125 Micron
Fiber Type	OS2, SM

Configuration

Connector Type	SC

Current

Insertion Loss	0.75 dB Max
Return Loss	26
Connectivity	Fiber Optic Connector

Dimensions

Display Size	2.5 mm

General

Color	Blue
Style	PROclick
Enclosure Type	Various
Sub Brand	OptiChannel
OEM Brand Name	Hubbell Premise Wiring
Specifications	• Cable Type - 900/250 µM • Ferrule Material - Zirconia ceramic, UPC polish • Fiber Type - UPC SM, OS2
UPC	662620224107
Material - Mounting Hardware	Fiber Termination, No Polish
Item Type	SC
Material	Ceramic

Logistics

Pallet Quantity	1610
Carton Quantity	10

Operational

Repeatability	0.1 dB
Adapter Type	SC
Temperature Rating	0C to 70C
Service Life	500 matings

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Catalog Page [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved