

VIS-8CHSMBOX

Smart Management Box

Features


- Integrated design, combining the SMSERVER, smart power management module, power supply switch, heater, fan, and warning light into one. Most IPC and IP Speaker models can be installed on the smart management box.
- Users can remotely monitor the working status of the smart management box and its loaded devices and receive alarm notifications via InVid Vision Live app and Vision CMS.
- Supports automatic restart of output port. When the smart management box detects a network disconnection, it will automatically power down the network devices and restart them.
- Supports manual restart of output port. If devices such as IPC or IP Speaker are faulty, users can manually restart the power supply output port via mobile app and Vision CMS.
- Equipped with surge protector, circuit breaker, and software protection function, forming a three layer protection mechanism to effectively resist risks such as lightning, short circuit, overvoltage, and overcurrent.

Model	VIS-8CHSMBOX
Power Input	
Input Type	AC 100 V to 240 V
Input Port	3 pin Connector, For the final installation, a UL 489 certified, 20 ampere circuit breaker must be be installed at the front end.
Power Output	
Socket	1 ch 5A, US socket
DC 12V	1 ch 2.5A, DC5521, Used for powering the router
PoE	8 RJ45 10M/100M self adaptive Ethernet Interface
PoE Power	Max 30 W for single port, Max 75 W in total
PoE Standard	IEEE 802.3at, IEEE 802.3af
Dedicated Power Interface (Pre Wired Internal Cabling)	
Fan Power Interface	DC12V, 2.5A
Heater Power Interface	AC 100 ~ 240V to DC 12V, 8A
NVR Power Interface	AC 100 ~ 240V to DC 48V, 2.3A
Router Power Interface	DC12V, 2.5A
Warning Light Power Interface	DC12V, 2.5A
Function	
System Functional Description	Overvoltage and Overload Protection,Power Information Collection,Power Switch Detection,Power Switch Control,Thermostatic Fan,Thermostatic Heater,Automatic Network Restart,Door Open Detection,Warning Light,Fault Reporting and Analysis
SMSERVER	
Decoding Format	Ultra 265, H.265, H.264
Decoding Capability	Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30
Audio Compression	G.711A, G.711U
Bandwidth	80 Mbps
Protocols	TCP/IP, P2P, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, RTSP, IPv6, IPv4

Ordering Information

VIS-8CHSMBOX: Smart Management Box

IP Video Input	8 ch
FTP/Schedule/Event Snapshot	4 ch snapshot (max. 8 MP (3840 × 2160) video resolution, with 1080P snapshot resolution)
Recording Resolution	16 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080P/960P/720P/D1/2CIF/CIF
Smart by IPC	Face Detection,Face Comparison,Vehicle Detection,SIP (Intrusion Detection, Cross Line Detection, Enter Area, Leave Area),Ultra Motion Detection (UMD),-Temperature Detection (Fire Detection, Smoking Detection, Temperature Measurement, Smoke and Fire Detection),People Counting (People Flow Counting, Crowd Density Monitoring),Video Metadata,Traffic Monitoring
Smart by SMBOX	Face Detection,Face Comparison,Ultra Motion Detection (UMD),Smart Intrusion Prevention (SIP)
VCA Search	Face Snapshot Search, Face Comparison Search, Motor Vehicle Search, Non Motor Vehicle Search, Human Body Search, General Search, People Counting Report, Heat Map, SmartSearch+, AcuSearch
by SMBOX with face detection cameras	8 ch
by SMBOX with normal cameras	2 ch
Vehicle Picture Library	Up to 5 vehicle picture libraries, with up to 25,000 vehicle pictures in total
SIP by SMBOX	4 ch
UMD by SMBOX	8 ch
Capacity of Snapshot Records	500 thousand records for face snapshot, One and a half millions records for SIP and vehicle
Alert Alarm	IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal, Array Damaged, Array Degraded
Network Interface	1 RJ45 10 M/100 M/1000 M self adaptive Ethernet Interface
USB	1 × USB2.0, 1 × USB3.0
ONVIF	Support
Hard Disk	
Hard Disk	1 x SATA interface, up to 16TB HDD (2.5" or 3.5"), or up to 4TB SSD (2.5")
Power Lightning Protector	
Maximum discharge current	40 kA
Rated discharge current	20 kA
Response time	L PE ≤ 25 ns, N PE ≤ 25 ns
General	
Surge Protection	6 kV
Working Temperature	When using HDDs: 40°F ~ 140°F (40°C ~ 60°C); When using SSDs: 40°F ~ 158°F (40°C ~ 70°C)
Working Humidity	≤ 90% RH (non condensing)
Weight (Without Camera)	≤ 35.27 lb (16 kg)
Dimensions (H x W x D)	25.6 x 16.7 x 9.1 in (650 × 424 × 230mm)
Slot dimensions	The space has a depth of 55mm and a width of 190mm for installing a 4G router, Select a 4G router with DC 12V round plug power supply, total power consumption not exceeding 30W, and at least 2 LAN ports.
Rating	IP56
Certification	CE EMC, FCC
Consumption	
No load power consumption	At ambient temperature of 25°C: 13.7 W (No HDD, No HDD heating, No Heater, No Fan, No Alarm Light)
Full load power consumption	At ambient temperature of 25°C: 247.2 W (16T HDD, HDD Heating, Heater, Full POE Output (75W), Fan, Alarm Light)
SMSERVER power consumption	At ambient temperature of 25°C: ≤8W (No HDD+ No POE Output) 96.5W (Full POE Output + 16T HDD) 122.2W (Full POE Output + 16T HDD + Heating Film)
Adaptable Mounting Bracket	
Left side	IVM-JB8/IVM-JB9, IVM-DRWM1/IVM-DRWM5/IVM-DRWM6/IVM-DRWM7
Right side	IVM-JB8/IVM-JB9, IVM-DRWM1/IVM-DRWM5/IVM-DRWM6/IVM-DRWM7
Bottom	One PTZ or One IP Speaker can be mounted. If mounting a PTZ, he box includes a PTZ pendent adapter. The threaded nipple attachment that comes with PTZs will screw into it.
Top	Support the installation of an IP speaker, no mounting bracket required. When mounting an IP speaker you will need to run the CAT cable down and through the water-tight grommets at the base of the box.
Other	Always suggested to use with a junction box. If your junction box isn't listed above you will need to use self tapping screws to connect



InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.