EPIC® H-B 24 AG

Article No.: 10102000

Panel-mount base; Design size: 24B; Connection design: Standard; Double lever; Number of cable entries: 1; Aluminum, Powder-coated; IP protection rating mounted: IP 65






Details

Benefits

- Safe fixing with 4 screws

Application

- Plant engineering
- Light & sound technology
- Plastics industry

Notes

© (2026) Lapp Group - all rights reserved.

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	EPIC®
Product type	Panel-mount base
Design size	24B
Delivery Unit	1
Industry segment	Building Automation
customs code	8536698000

Electrical parameters

Product design

With cable gland	No
Number of cable entries	1 pc.
Number of cable entries at the top	1
Number of cable entries sideways	0
With levers	Yes
Locking mechanism	Double lever
Number of locking bolts	0
Total length	4.724 in
Overall width	1.693 in
Overall height	1.094 in
Type of housing	Panel-mount base
Connector housing design	Straight

© (2026) Lapp Group - all rights reserved.

With thread	No
With hinged lid	No
Connection design	Standard
With neck	No
Screen contact	No
EMC shielding	No
Housing main material	Aluminum
Housing base material, short form	Al
Housing coating	Powder-coated
Lever material	Steel
Material sealing	Acrylonitrile butadiene rubber
Colour housing	gray
Housing RAL color	RAL 9006

Product features

IP protection rating mounted	IP 65
Short-term temperature peaks	125 °C
Operating temperature min.	-40 °C
Operating temperature max.	100 °C
UV-resistant	Yes
Chemical resistant	No
Acid-resistant	No
Corrosion-resistant according to	DIN EN 6988
corrosion resistant	Yes
Halogenfree	Yes
Impact proof	Yes
Vibration protection	Yes

Certifications and standards

CE marking	Yes
UR recognized	Yes

© (2026) Lapp Group - all rights reserved.

UR certification	according to UL 1977 (e-file number: E75770) according to UL 50E (e-file number: E75770)
UL category control number	ECBT2
cUR recognized	Yes
cUR certification	according to CSA C22.2 No. 182.3 (e-file number: E75770)
cUR category control number	ECBT8
CSA certified	No
VDE certified	Yes
VDE registration number	B437
Product standard according to IEC	IEC 61984
TÜV certified	No

© (2026) Lapp Group - all rights reserved.

EPIC® H-B 24 AG

Article No.	Name	Delivery Unit
10102000	EPIC® H-B 24 AG	1

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.