H-BE BCEM AG 1.5 FEMALE CONTACT (100)

Article No.: 11195200

Turned contact; Socket; Crimp termination; For cross-section (min./max.): 1.5mm² - 1.5 mm²; For cross-section (min./max.): 1.5 mm²; Brass Silver-plated



Details

Benefits

- High-quality, solid or twisted contact for the safe transmission of higher currents.
- Crimp termination creates a vibration-proof connection, provides maximum contact protection between the contact and cable and is suitable for automated assembly.
- With silver or gold-plated contact surface. Silver-plated contacts for maximum electrical conductivity and good thermal conductivity; gold-plated contacts for corrosion protection and longer service life.
- UL certification according to technical data enables the product to be used on the North American market.

Application

- For use with many EPIC® rectangular connector inserts and in the EPIC® MH modular system.

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

© (2026) Lapp Group - all rights reserved.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	EPIC®
Product type	Turned contact
Contact delivery type	Bag
Delivery Unit	100
Mounting method	crimp
Industry segment	Building Automation
customs code	8536904000

Electrical parameters

Product design

Contact diameter	0.098 in
Contact variant	Socket
Contact manufacturing method	Machined
Connection type conductor	Crimp termination
Stripping length of single conductor	0.315 in
Cross-section ratio	2
Connectable conductor cross section min. (AWG)	16 AWG
Max. connectable conductor cross-section AWG	16 AWG
Connectable conductor cross section (mm2)	1.5 mm^2
Min. connectable conductor cross-section (mm2) (in2)	1.5 mm^2
Max. connectable conductor cross-section (mm2) (in2)	1.5 mm^2
Material contact	Brass

© (2026) Lapp Group - all rights reserved.

Contact material, short form	CuZn
Contact coating material	Silver-plated
Contact coating material, short form	Ag

Product features

Certifications and standards

CE marking	No
EAC certified	Not required
EAC certification number	Отказное письмо № 39
UR recognized	Yes
UL category control number	ECBT2
cUR recognized	Yes
cUR category control number	ECBT8
CSA certified	No
VDE certified	No
Product standard according to IEC	IEC 61984
TÜV certified	No

© (2026) Lapp Group - all rights reserved.

EPIC® H-BE 2.5 machined contacts

Article No.	Name	Contact variant	Contact coating material	Min. connectable conductor cross-section (mm2) (in2)	Max. connectable conductor cross-section (mm2) (in2)	Delivery Unit
11190000	H-BE SCEM AG 0.5 MALE CONTACT (100)	Pin	Silver-plated	0.5 mm^2	0.5 mm^2	100
11190100	H-BE SCEM AG 0.75-1.0 MALE CONTACT (100)	Pin	Silver-plated	0.75 mm^2	1 mm^2	100
11190200	H-BE SCEM AG 1.5 MALE CONTACT	Pin	Silver-plated	1.5 mm^2	1.5 mm^2	100
11190300	EPIC® H-BE SCEM AG 2.5 (100)	Pin	Silver-plated	2.5 mm^2	2.5 mm^2	100
11190301	EPIC® H-BE SCEM AU 0.14-0,37(100)	Pin	Gold-plated	0.14 mm^2	0.37 mm^2	100
11190302	EPIC® H-BE BCEM AU 0,14-0,37 (100)	Socket	Gold-plated	0.14 mm^2	0.37 mm^2	100
11190400	H-BE SCEM AG 4.0 MALE CONTACT (100)	Pin	Silver-plated	4 mm^2	4 mm^2	100
11192000	H-BE SCEM AU 0.5 MALE CONTACT (100)	Pin	Gold-plated	0.5 mm^2	0.5 mm^2	100
11192100	H-BE SCEM AU 0.75-1.0 MALE CONTACT (100)	Pin	Gold-plated	0.75 mm^2	1 mm^2	100
11192200	H-BE SCEM AU 1.5 MALE CONTACT (100)	Pin	Gold-plated	1.5 mm^2	1.5 mm^2	100
11192300	H-BE SCEM AU 2.5 (100)	Pin	Gold-plated	2.5 mm^2	2.5 mm^2	100
11195000	H-BE BCEM AG 0.5 FEMALE CONTACT (100)	Socket	Silver-plated	0.5 mm^2	0.5 mm^2	100
11195100	H-BE BCEM AG 0.75-1.0 FEMALE CONT (100)	Socket	Silver-plated	0.75 mm^2	1 mm^2	100
11195200	H-BE BCEM AG 1.5 FEMALE CONTACT (100)	Socket	Silver-plated	1.5 mm^2	1.5 mm^2	100
11195300	EPIC® H-BE BCEM AG 2.5 (100)	Socket	Silver-plated	2.5 mm^2	2.5 mm^2	100
11195400	EPIC® H-BE BCEM AG 4.0 (100)	Socket	Silver-plated	4 mm^2	4 mm^2	100
11197000	H-BE BCEM AU 0.5 FEMALE CONTACT (100)	Socket	Gold-plated	0.5 mm^2	0.5 mm^2	100
11197100	H-BE BCEM AU 0.75-1.0 FEMALE CONT (100)	Socket	Gold-plated	0.75 mm^2	1 mm^2	100
11197200	H-BE BCEM AU 1.5 FEMALE CONTACT (100)	Socket	Gold-plated	1.5 mm^2	1.5 mm^2	100
11197300	H-BE BCEM AU 2.5 FEMALE CONTACT (100)	Socket	Gold-plated	2.5 mm^2	2.5 mm^2	100

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.