EPIC® H-D SCEG AG 1.5-2.5 (100)

Article No.: 11223500

Stamped contact; Pin; Crimp termination; For cross-section (min./max.): 1.5mm² - 2.5 mm²; Brass Silver-plated



Details

Benefits

- Punched contact: established and inexpensive.
- Crimp termination creates a vibration-proof connection, provides maximum contact protection between the contact and cable and is suitable for automated assembly.
- With silver or gold-plated contact surface. Silver-plated contacts for maximum electrical conductivity and good thermal conductivity; gold-plated contacts for corrosion protection and longer service life.

Application

- For use with rectangular connector inserts of the EPIC®H-D series.

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

© (2026) Lapp Group - all rights reserved.

Technical Data

General information

Brand	EPIC®
Product type	Stamped contact
Contact delivery type	Bag
Delivery Unit	100
Mounting method	crimp
customs code	8536698000

Electrical parameters

Product design

Contact diameter	0.063 in
Contact variant	Pin
Contact manufacturing method	Stamped
Connection type conductor	Crimp termination
Stripping length of single conductor	0.157 in
Connectable conductor cross section min. (AWG)	16 AWG
Max. connectable conductor cross-section AWG	14 AWG
Min. connectable conductor cross-section (mm2) (in2)	1.5 mm^2
Max. connectable conductor cross-section (mm2) (in2)	2.5 mm^2
Material contact	Brass
Contact material, short form	CuZn
Contact coating material	Silver-plated
Contact coating material, short form	Ag

Product features

© (2026) Lapp Group - all rights reserved.

Certifications and standards	
CE marking	No
EAC certified	Not required
EAC certification number	Отказное письмо № 39
UR recognized	No
cUR recognized	No
CSA certified	No
VDE certified	No
Product standard according to IEC	IEC 61984
TÜV certified	No

© (2026) Lapp Group - all rights reserved.

EPIC® H-D 1,6 stamped contacts

Article No.	Name	Contact variant	Contact coating material	Min. connectable conductor cross-section (mm2) (in2)	Max. connectable conductor cross-section (mm2) (in2)	Delivery Unit
11221000	EPIC® H-D SCEG AG 0.5-1.5 (100)	Pin	Silver-plated	0.5 mm²	1.5 mm²	100
11221300	EPIC® H-D SCEG AU 0.5-1.5 (100)	Pin	Gold-plated	0.5 mm²	1.5 mm²	100
11223500	EPIC® H-D SCEG AG 1.5-2.5 (100)	Pin	Silver-plated	1.5 mm²	2.5 mm²	100
11228500	EPIC® H-D BCEG AG 1.5-2.5 (100)	Socket	Silver-plated	1.5 mm²	2.5 mm²	100
11231100	EPIC® H-D BCEG AG 0.14-0.5 (100)	Socket	Silver-plated	0.14 mm²	0.5 mm²	100
11233100	EPIC® H-D BCEG AU 0.14-0.5 (100)	Socket	Gold-plated	0.14 mm²	0.5 mm²	100
11236100	EPIC® H-D BCEG AG 0.5-1.5 (100)	Socket	Silver-plated	0.5 mm²	1.5 mm²	100
11238100	EPIC® H-D BCEG AU 0.5-1.5 (100)	Socket	Gold-plated	0.5 mm²	1.5 mm²	100
11241100	EPIC® H-D SCEG AG 0.14-0.5 (100)	Pin	Silver-plated	0.14 mm²	0.5 mm²	100
11243100	EPIC® H-D SCEG AU 0.14-0.5 (100)	Pin	Gold-plated	0.14 mm²	0.5 mm²	100

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.