SKINDICHT® SK PG 16

Article No.: 52004260

Cable gland; PG 16; Clamping range (min./max.): 0.512 - 0.709 in; Wrench size 1: 0.945; Brass Nickel-plated; Halogenfree; UV-resistant; IP 20;



Details

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	SKINDICHT®
Product type	Cable gland
Delivery with lock nut	No
Including o-ring	No

© (2026) Lapp Group - all rights reserved.

Type of packaging	Bag
Delivery Unit	25
Mounting method	in threaded borehole
customs code	7419805050

Electrical parameters

Product design

For armored cables	No
Glass-fibre reinforced	No
Number of cable entries	1 pc.
With bending protection	No
Cable gland design	Straight
Total length	0.827 in
Overall width	1.417 in
Clear width	0.709 in
Thread type	PG
Thread size	PG 16
Pitch of thread	1,41
Thread length	0.295 in
Wrench size 1	0.945 in
Hexagon corner dimensions	1.075 in
Wrench width	0.945 in
Min. clamping range	0.512 in
Max. clamping range	0.709 in
EMC shielding	No
Body material	Brass
Body material, short form	CuZn
Surface protection	Nickel-plated
Colour description	metal

© (2026) Lapp Group - all rights reserved.

Product features

IP protection rating	IP 20
Suitable for EX-applications	No
Temperature static min.	-60 °C
Max. static temperature	200 °C
Temperature (min.)	-60 °C
Temperature (max.)	200 °C
Flame-retardant	Yes
UV-resistant	Yes
Halogenfree	Yes
Oil resistant	Yes
lead free	No
Strain relief	Yes

Certifications and standards

CE marking	Yes
UL recognized	No
UL listed	No
cUR recognized	No
cUL listed	No
CSA certified	No
VDE certified	No
For Ex zone gas	without
For Ex-zone dust	without
GGVS certified	No
DNV-certified	No
Ecolab certified	No
NSF certified	No
EHEDG certified	No

© (2026) Lapp Group - all rights reserved.

SKINDICHT® SK

Article No.	Name	Thread size	Thread length	Min. clamping range	Max. clamping range	Wrench size 1	Delivery Unit
51712740	SKINDICHT® SK PG 29	PG 29	0.315 in	0.787 in	1.22 in	1.614 in	10
52004230	SKINDICHT® SK PG 9	PG 9	0.236 in	0.236 in	0.472 in	0.669 in	50
52004240	SKINDICHT® SK PG 11	PG 11	0.236 in	0.276 in	0.591 in	0.787 in	50
52004250	SKINDICHT® SK PG 13.5	PG 13,5	0.295 in	0.472 in	0.63 in	0.866 in	25
52004260	SKINDICHT® SK PG 16	PG 16	0.295 in	0.512 in	0.709 in	0.945 in	25
52004270	SKINDICHT® SK PG 21	PG 21	0.315 in	0.591 in	0.906 in	1.181 in	25

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.