SKINDICHT® SM-M 25X1.5 LOCKNUT

Article No.: 52103030

Lock nut; M 25; Wrench width: 1.181in; Brass Nickel-plated



Details

Benefits

- Available in sizes M6x1 to M110x2.
- Item numbers ending with “LF” are lead-free product alternatives with otherwise identical product properties. “Lead-free” items do not include lead, which is currently permitted to account for up to four per cent in copper alloys, but could in future be banned in accordance with the RoHS directive.

Application

- For locking a SKINTOP® /SKINDICHT® cable gland on the inside of the application (e.g. housing).
- For thin-walled housings without a thread, which only allow one through-hole.
- Withstands high chemical and mechanical loads.

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

© (2026) Lapp Group - all rights reserved.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	SKINDICHT®
Product type	Lock nut
Type of packaging	Bag
Delivery Unit	100
Industry segment	Construction Machinery Food & Beverage Healthcare & Pharma Heating, Ventilation, Air Conditioning & Refrigeration Machine Tools Ships & boats Building Automation
customs code	7415330500

Electrical parameters

Product design

Glass-fibre reinforced	No
Thickness	0.157 in
Thread type	Metric
Thread size	M 25
Pitch of thread	1,5
Thread standard	DIN EN 60423
Hexagon corner dimensions	1.299 in
Wrench width	1.181 in
EMC shielding	No
Body material	Brass
Body material, short form	CuZn

© (2026) Lapp Group - all rights reserved.

Surface protection	Nickel-plated
Colour description	metal

Product features

Suitable for EX-applications	No
Temperature (min.)	-60 °C
Temperature (max.)	200 °C
Flame-retardant	Yes
UV-resistant	Yes
Chemical resistant	Yes
Halogenfree	Yes
Oil resistant	Yes
lead free	No
Impact proof	Yes

Certifications and standards

CE marking	Yes
EAC certified	Not required
EAC certification number	Отказное письмо № 43
UL recognized	No
UL listed	No
cUR recognized	No
cUL listed	No
CSA certified	No
VDE certified	No
GGVS certified	No
Tested for fire protection for railway vehicles	No
Ecolab certified	No
NSF certified	No
FDA certified	No
EHEDG certified	No

© (2026) Lapp Group - all rights reserved.

SKINDICHT® SM-M

Article No.	Name	Thread size	Wrench width	Delivery Unit
52102997	SKINDICHT® SM-M 8X1 LOCKNUT	M 8	0.512 in	50
52102998	SKINDICHT® SM-M 6X1 LOCKNUT	M 6	0.394 in	50
52102999	SKINDICHT® SM-M 10X1 LOCKNUT	M 10	0.669 in	50
52103000	SKINDICHT® SM-M 12X1.5 LOCKNUT	M 12	0.591 in	100
52103000LF	SKINDICHT® SM-M 12X1.5 LOCKNUT	M 12	0.591 in	100
52103010	SKINDICHT® SM-M 16X1.5 LOCKNUT	M 16	0.748 in	100
52103010LF	SKINDICHT® SM-M 16X1.5 LOCKNUT	M 16	0.748 in	100
52103020	SKINDICHT® SM-M 20X1.5 LOCKNUT	M 20	0.945 in	100
52103020LF	SKINDICHT® SM-M 20X1.5 LOCKNUT	M 20	0.945 in	100
52103030	SKINDICHT® SM-M 25X1.5 LOCKNUT	M 25	1.181 in	100
52103030LF	SKINDICHT® SM-M 25X1.5 LOCKNUT	M 25	1.181 in	100
52103040	SKINDICHT® SM-M 32X1.5 LOCKNUT	M 32	1.417 in	100
52103040LF	SKINDICHT® SM-M 32X1.5 LOCKNUT	M 32	1.417 in	100
52103050	SKINDICHT® SM-M 40X1.5 LOCKNUT	M 40	1.811 in	50
52103050LF	SKINDICHT® SM-M 40X1.5 LOCKNUT	M 40	1.811 in	50
52103060	SKINDICHT® SM-M 50X1.5 LOCKNUT	M 50	2.362 in	50
52103060LF	SKINDICHT® SM-M 50X1.5 LOCKNUT	M 50	2.362 in	50
52103070	SKINDICHT® SM-M 63X1.5 LOCKNUT	M 63	2.756 in	25
52103070LF	SKINDICHT® SM-M 63X1.5 LOCKNUT	M 63	2.756 in	25
52103071	SKINDICHT® SM-M 75X1.5 LOCKNUT	M 75	3.346 in	1
52103072	SKINDICHT® SM-M 90X2 LOCKNUT	M 90	4.016 in	1
52103073	SKINDICHT® SM-M110X2 LOCKNUT	M 110	4.882 in	1

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.