SKINDICHT® MA-PG/M 16/20X1.5 FLAT

Article No.: 52104495

Adapter; Inner thread: M 20; Outer thread: PG 16; Brass Nickel-plated



Details

Benefits

- Allows for a simple transition from a PG outer thread to a metric inner thread.
- Withstands temperatures up to +200°C.
- Available for thread sizes up to PG36 or M40.
- Form A with knurled shape for easy insertion of the adapter, even in oily environments. Form B with a smooth variant.
- Item numbers ending with “LF” are lead-free product alternatives with otherwise identical product properties. “Lead-free” items do not include lead, which is currently permitted to account for up to four per cent in copper alloys, but could in future be banned in accordance with the RoHS directive.

Application

- For applications where different thread types are used.
- Withstands high chemical and mechanical loads.
- Suitable for outdoor use.

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

© (2026) Lapp Group - all rights reserved.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	SKINDICHT®
Product type	Adapter
Delivery with lock nut	No
Including o-ring	No
Type of packaging	Bag
Delivery Unit	50
Mounting method	in threaded borehole
customs code	7419805050

Electrical parameters

Product design

Cable gland design	Straight
Inner thread	M 20
Outer thread	PG 16
Total length	0.374 in
Overall width	0.945 in
Clear width	0.669 in
Thread size	PG 16
Pitch of thread	1,41
Thread length	0.256 in
Thread standard	DIN EN 60423
Body material	Brass
Body material, short form	CuZn
Surface protection	Nickel-plated

© (2026) Lapp Group - all rights reserved.

Product features

Suitable for EX-applications	No
Temperature (min.)	-60 °C
Temperature (max.)	200 °C
Flame-retardant	Yes
UV-resistant	Yes
Chemical resistant	Yes
Halogenfree	Yes
Oil resistant	Yes
lead free	No

Certifications and standards

CE marking	Yes
UL recognized	No
UL listed	No
cUR recognized	No
cUL listed	No
CSA certified	No
VDE certified	No
GGVS certified	No
Ecolab certified	No
NSF certified	No
FDA certified	No
EHEDG certified	No

© (2026) Lapp Group - all rights reserved.

SKINDICHT® MA-PG/M

Article No.	Name	Outer thread	Inner thread	Delivery Unit
52104490	SKINDICHT® MA-PG/M 7/12X1.5 HIGH	PG 7	M 12	100
52104490LF	SKINDICHT® MA-PG/M 7/12x1,5 HIGH	PG 7	M 12	100
52104491	SKINDICHT® MA-PG/M 9/16X1.5 HIGH	PG 9	M 16	50
52104491LF	SKINDICHT® MA-PG/M 9/16x1,5 HIGH	PG 9	M 16	50
52104492	SKINDICHT® MA-PG/M 11/16X1.5 FLAT	PG 11	M 16	50
52104492LF	SKINDICHT® MA-PG/M 11/16x1,5 FLAT	PG 11	M 16	50
52104493	SKINDICHT® MA-PG/M 11/20X1.5 HIGH	PG 11	M 20	50
52104493LF	SKINDICHT® MA-PG/M 11/20x1,5 HIGH	PG 11	M 20	50
52104494	SKINDICHT® MA-PG/M 13.5/20X1.5 HIGH	PG 13,5	M 20	50
52104494LF	SKINDICHT® MA-PG/M 13,5/20x1,5 HIGH	PG 13,5	M 20	50
52104495	SKINDICHT® MA-PG/M 16/20X1.5 FLAT	PG 16	M 20	50
52104495LF	SKINDICHT® MA-PG/M 16/20x1,5 FLAT	PG 16	M 20	50
52104496	SKINDICHT® MA-PG/M 16/25X1.5 HIGH	PG 16	M 25	50
52104496LF	SKINDICHT® MA-PG/M 16/25x1,5 HIGH	PG 16	M 25	50
52104497	SKINDICHT® MA-PG/M 21/20X1.5 FLAT	PG 21	M 20	50
52104497LF	SKINDICHT® MA-PG/M 21/20x1,5 flach	PG 21	M 20	50
52104498	SKINDICHT® MA-PG/M 21/25X1.5 FLAT	PG 21	M 25	50
52104498LF	SKINDICHT® MA-PG/M 21/25x1,5 flach	PG 21	M 25	50
52104499	SKINDICHT® MA-PG/M 21/32X1.5 HIGH	PG 21	M 32	50
52104499LF	SKINDICHT® MA-PG/M 21/32x1,5 HIGH	PG 21	M 32	50
52104500	SKINDICHT® MA-PG/M 29/25X1.5 FLAT	PG 29	M 25	25
52104500LF	SKINDICHT® MA-PG/M 29/25x1,5 FLAT	PG 29	M 25	25
52104501	SKINDICHT® MA-PG/M 29/32X1.5 FLAT	PG 29	M 32	25
52104501LF	SKINDICHT® MA-PG/M 29/32x1,5 FLAT	PG 29	M 32	25
52104502	SKINDICHT® MA-PG/M 29/40X1.5 HIGH	PG 29	M 40	10
52104502LF	SKINDICHT® MA-PG/M 29/40x1,5 hoch	PG 29	M 40	10
52104503	SKINDICHT® MA-PG/M 36/40X1.5 FLAT	PG 36	M 40	10
52104503LF	SKINDICHT® MA-PG/M 36/40x1,5 FLAT	PG 36	M 40	10

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.