SKINDICHT® SKZ-M 25X1.5/21

Article No.: 52106840

Cable gland; M 25; Clamping range (min./max.): 0.433 - 0.787 in; Wrench size 1: 1.181; Brass Nickel-plated; UV-resistant; IP 55;



Details

Application

- Plant engineering

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	SKINDICHT®

© (2026) Lapp Group - all rights reserved.

Product type	Cable gland
Scope of delivery	including O-ring
Delivery with lock nut	No
Including o-ring	Yes
Type of packaging	Bag
Delivery Unit	25
Mounting method	in threaded borehole
Industry segment	Energy
customs code	7419805050

Electrical parameters

Product design

For armored cables	No
Glass-fibre reinforced	Yes
Number of cable entries	1 pc.
With bending protection	No
Cable gland design	Straight
Total length	1.614 in
Overall width	1.811 in
Clear width	0.787 in
Thread type	Metric
Thread size	M 25
Pitch of thread	1,5
Thread length	0.276 in
Thread standard	DIN EN 60423
Wrench size 1	1.181 in
Wrench size 2	1.181 in
Hexagon corner dimensions	1.339 in
Min. clamping range	0.433 in
Max. clamping range	0.787 in
EMC shielding	No
Seal type	Incized sealing ring

© (2026) Lapp Group - all rights reserved.

Thread-side sealing element	O-ring
Cable-side sealing element	Incized sealing ring
Material o-ring	Acrylonitrile butadiene rubber
O-ring material, short form	NBR
Material sealing	Chloroprene rubber
Body material	Brass
Body material, short form	CuZn
Surface protection	Nickel-plated
Colour description	metal

Product features

IP protection rating	IP 55
Suitable for EX-applications	No
Temperature static min.	-20 °C
Max. static temperature	80 °C
Temperature (min.)	-20 °C
Temperature (max.)	80 °C
Flame-retardant	No
UV-resistant	Yes
Halogenfree	No
Oil resistant	Yes
lead free	No
Impact proof	Yes
Strain relief	Yes

Certifications and standards

CE marking	Yes
UL recognized	No
UL listed	No
cUR recognized	No
cUL listed	No
CSA certified	No
VDE certified	No

© (2026) Lapp Group - all rights reserved.

For Ex zone gas	without
For Ex-zone dust	without
GGVS certified	No
DNV-certified	No
Ecolab certified	No
NSF certified	No
EHEDG certified	No

© (2026) Lapp Group - all rights reserved.

SKINDICHT® SKZ-M

Article No.	Name	Thread size	Thread length	Min. clamping range	Max. clamping range	Wrench size 1	Delivery Unit
52106800	SKINDICHT® SKZ-M 16X1.5/9	M 16	0.197 in	0.197 in	0.315 in	0.709 in	50
52106810	SKINDICHT® SKZ-M 20X1.5/11	M 20	0.236 in	0.276 in	0.394 in	0.866 in	50
52106820	SKINDICHT® SKZ-M 20X1.5/13.5	M 20	0.236 in	0.276 in	0.512 in	0.866 in	25
52106830	SKINDICHT® SKZ-M 20X1.5/16	M 20	0.236 in	0.315 in	0.531 in	0.945 in	25
52106840	SKINDICHT® SKZ-M 25X1.5/21	M 25	0.276 in	0.433 in	0.787 in	1.181 in	25
52106850	SKINDICHT® SKZ-M 32X1.5/29	M 32	0.315 in	0.709 in	1.063 in	1.575 in	10

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.