SKINTOP® CLICK 25 RAL 9005 BK

Article No.: 53112884

Cable gland; Borehole diameter: 0.996in; Clamping range (min./max.): 0.354in - 0.669in; Wrench size 1: 1.26in; black; Polyamide Uncoated; UV-resistant; IP 68 - 5 g/cm² (30 min)






Details

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

© (2026) Lapp Group - all rights reserved.

Technical Data

General information

Brand	SKINTOP®
Product type	Cable gland
Scope of delivery	including disassembly tool
Delivery with lock nut	No
Including o-ring	No
Type of packaging	Bag
Delivery Unit	25
Mounting method	click
Industry segment	Agricultural & Farm Machinery Healthcare & Pharma Heating, Ventilation, Air Conditioning & Refrigeration Ships & boats Building Automation
customs code	3926909985

Electrical parameters

Product design

For armored cables	No
Glass-fibre reinforced	No
Number of cable entries	1 pc.
With bending protection	No
Cable gland design	Straight
Total length	1.89 in
Clear width	0.669 in
Borehole diameter	0.996 in
Panel thickness (min.)	0.039 in
Wall thickness (max.)	0.157 in
Thread type	without
Thread size	M 25

© (2026) Lapp Group - all rights reserved.

Thread length	0.315 in
Wrench size 1	1.26 in
Wrench size 2	1.181 in
Hexagon corner dimensions	1.386 in
Min. clamping range	0.354 in
Max. clamping range	0.669 in
EMC shielding	No
Seal type	Conduit Sealing Ring
Thread-side sealing element	Flat seal
Material sealing	Chloroprene rubber
Body material	Polyamide
Body material, short form	PA
Surface protection	Uncoated
Colour description	black
RAL color	RAL 9005

Product features

IP protection rating	IP 68 - 5 g/cm² (30 min)
NEMA classification type	Type 1 Type 12
Suitable for EX-applications	No
Temperature dynamic min.	-20 °C
Max. dynamic temperature	100 °C
Temperature static min.	-40 °C
Max. static temperature	100 °C
Temperature (min.)	-40 °C
Temperature (max.)	100 °C
Flame-retardant	Yes
Flame retardance according to	UL 94 V-2
UV-resistant	Yes
Chemical resistant	Yes
Acid-resistant	No
Halogenfree	No
Oil resistant	Yes

© (2026) Lapp Group - all rights reserved.

Impact proof	Yes
Vibration protection	Yes
Strain relief	Yes

Certifications and standards

CE marking	Yes
UL recognized	No
UL listed	Yes
UL certification	according to UL 514B (CCN: QBPZ / e-file number: E79903)
cUR recognized	No
cUL listed	Yes
cUL certification	according to CSA C22.2 No. 18.3 (CCN: QBPZ7 / e-file number: E79903)
CSA certified	No
VDE certified	Yes
VDE registration number	40020892
For Ex zone gas	without
For Ex-zone dust	without
GGVS certified	No
DNV-certified	Yes
DNV certificate number	TAE00002M4
Tested for fire protection for railway vehicles	No
Ecolab certified	No
NSF certified	No
FDA certified	No
EHEDG certified	No

© (2026) Lapp Group - all rights reserved.

SKINTOP® CLICK / SKINTOP® CLICK-R

Article No.	Name	Thread length	Wrench size 1	Thread size	Min. clamping range	Max. clamping range	Colour description	Delivery Unit
53112686	SKINTOP® CLICK 16 RAL 7035 LGY	0.315 in	0.866 in	M 16	0.197 in	0.354 in	light gray	50
53112687	SKINTOP® CLICK 20 RAL 7035 LGY	0.315 in	1.063 in	M 20	0.276 in	0.512 in	light gray	25
53112688	SKINTOP® CLICK 25 RAL 7035 LGY	0.315 in	1.26 in	M 25	0.354 in	0.669 in	light gray	25
53112689	SKINTOP® CLICK-R 16 RAL 7035 LGY	0.315 in	0.866 in	M 16	0.157 in	0.276 in	light gray	50
53112690	SKINTOP® CLICK-R 20 RAL 7035 LGY	0.315 in	1.063 in	M 20	0.197 in	0.394 in	light gray	25
53112691	SKINTOP® CLICK-R 25 RAL 7035 LGY	0.315 in	1.26 in	M 25	0.236 in	0.512 in	light gray	25
53112692	SKINTOP® CLICK 12 RAL 7035 LGY	0.315 in	0.709 in	M 12	0.177 in	0.276 in	light gray	50
53112694	SKINTOP® CLICK 32 RAL 7035 LGY	0.315 in	1.575 in	M 32	0.433 in	0.787 in	light gray	25
53112876	SKINTOP® CLICK 16 RAL 7001 SGY	0.315 in	0.866 in	M 16	0.197 in	0.354 in	silver gray	50
53112877	SKINTOP® CLICK 20 RAL 7001 SGY	0.315 in	1.063 in	M 20	0.276 in	0.512 in	silver gray	25
53112878	SKINTOP® CLICK 25 RAL 7001 SGY	0.315 in	1.26 in	M 25	0.354 in	0.669 in	silver gray	25
53112879	SKINTOP® CLICK-R 16 RAL 7001 SGY	0.315 in	0.866 in	M 16	0.157 in	0.276 in	silver gray	50
53112880	SKINTOP® CLICK-R 20 RAL 7001 SGY	0.315 in	1.063 in	M 20	0.197 in	0.394 in	silver gray	25
53112881	SKINTOP® CLICK-R 25 RAL 7001 SGY	0.315 in	1.26 in	M 25	0.236 in	0.512 in	silver gray	25
53112882	SKINTOP® CLICK 16 RAL 9005 BK	0.315 in	0.866 in	M 16	0.197 in	0.354 in	black	50
53112883	SKINTOP® CLICK 20 RAL 9005 BK	0.315 in	1.063 in	M 20	0.276 in	0.512 in	black	25
53112884	SKINTOP® CLICK 25 RAL 9005 BK	0.315 in	1.26 in	M 25	0.354 in	0.669 in	black	25
53112885	SKINTOP® CLICK-R 16 RAL 9005 BK	0.315 in	0.866 in	M 16	0.157 in	0.276 in	black	50
53112886	SKINTOP® CLICK-R 20 RAL 9005 BK	0.315 in	1.063 in	M 20	0.197 in	0.394 in	black	25
53112887	SKINTOP® CLICK-R 25 RAL 9005 BK	0.315 in	1.26 in	M 25	0.236 in	0.512 in	black	25
53112921	SKINTOP® CLICK 12 RAL 7001 SGY	0.315 in	0.709 in	M 12	0.177 in	0.276 in	silver gray	50
53112922	SKINTOP® CLICK 32 RAL 7001 SGY	0.315 in	1.575 in	M 32	0.433 in	0.787 in	silver gray	25
53112923	SKINTOP® CLICK 12 RAL 9005 BK	0.315 in	0.709 in	M 12	0.177 in	0.276 in	black	50
53112924	SKINTOP® CLICK 32 RAL 9005 BK	0.315 in	1.575 in	M 32	0.433 in	0.787 in	black	25
53112925	SKINTOP® CLICK-R 12 RAL 7035 LGY	0.315 in	0.709 in	M 12	0.138 in	0.197 in	light gray	50
53112926	SKINTOP® CLICK-R 32 RAL 7035 LGY	0.315 in	1.575 in	M 32	0.276 in	0.591 in	light gray	25
53112927	SKINTOP® CLICK-R 12 RAL 7001 SGY	0.315 in	0.709 in	M 12	0.138 in	0.197 in	silver gray	50
53112928	SKINTOP® CLICK-R 32 RAL 7001 SGY	0.315 in	1.575 in	M 32	0.276 in	0.591 in	silver gray	25
53112929	SKINTOP® CLICK-R 12 RAL 9005 BK	0.315 in	0.709 in	M 12	0.138 in	0.197 in	black	50
53112931	SKINTOP® CLICK-R 32 RAL 9005 BK	0.315 in	1.575 in	M 32	0.276 in	0.591 in	black	25

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.