SKINTOP® DIX-M 40969

Article No.: 53340969

Multiple sealing insert; M 40; Number of cable entries: 9pc.; Borehole diameter: 0.272in; black






Details

Benefits

- Easy insertion of several cables using one cable gland.
- Multi-entry of cables allows a higher packing density.
- Gentle clamping of the cables due to high elasticity of the sealing insert material.
- Protection class IP 68 can be achieved if all boreholes are occupied by cables with rated diameter and unused openings are closed with SKINTOP® DIX-DV sealing plugs.
- Numerous variants available, depending on the number and diameter of cables. Made of acrylonitrile butadiene rubber (NBR), fluorinated rubber (FKM) or silicone (SI).
- The NBR variants are oil resistant.

© (2026) Lapp Group - all rights reserved.

- The FKM variants are resistant to aggressive media such as alkaline solutions, acids, solvents as well as oils. They are extremely heat resistant and suitable for use at extremely hot temperatures (up to +200°C).
- The silicone variants are resistant to ECOLAB® cleaning agents and disinfectants and are highly chemical resistant. They comply with FDA 21 CFR 177.2600 and are therefore approved for use in the food and beverage industry. Their blue color makes them easy to distinguish from food. They are also extremely flexible at cold temperatures and suitable for use at extreme sub-zero temperatures (down to -50°C.

Application

- For use with metric SKINTOP®/SKINTOP® CLICK cable glands.
- Suitable for outdoor use.

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	SKINTOP®
Product type	Multiple sealing insert
Type of packaging	Bag
Delivery Unit	25
Industry segment	Assembly Machines Heating, Ventilation, Air Conditioning & Refrigeration Lifts & Elevators
customs code	4016935050

Electrical parameters

© (2026) Lapp Group - all rights reserved.

Product design

Number of cable entries	9 pc.
Slotted	No
Overall height	0.571 in
Borehole diameter	0.272 in
Thread size	M 40
EMC shielding	No
Material	Acrylonitrile butadiene rubber
Colour description	black

Product features

IP protection rating	IP 68 - 5 g/cm² (30 min) IP 54
Suitable for EX-applications	No
Temperature (min.)	-40 °C
Temperature (max.)	100 °C
Flame-retardant	No
UV-resistant	No
Chemical resistant	Yes
Acid-resistant	No
Halogenfree	Yes
Oil resistant	Yes

Certifications and standards

CE marking	Yes
Ecolab certified	No

© (2026) Lapp Group - all rights reserved.

SKINTOP® DIX-M

Article No.	Name	Thread size	Borehole diameter	Number of cable entries	Material	Delivery Unit
53316220	SKINTOP® DIX-M 16220	M 16	0.079 in	2 pc.	Acrylonitrile butadiene rubber	100
53316230	SKINTOP® DIX-M 16230	M 16	0.118 in	2 pc.	Acrylonitrile butadiene rubber	100
53316240	SKINTOP® DIX-M 16240	M 16	0.157 in	2 pc.	Acrylonitrile butadiene rubber	100
53316300	SKINTOP® DIX-M 16220 SI	M 16	0.079 in	2 pc.	Silicone	100
53316301	SKINTOP® DIX-M 16230 SI	M 16	0.118 in	2 pc.	Silicone	100
53316302	SKINTOP® DIX-M 20250 SI	M 20	0.197 in	2 pc.	Silicone	100
53316303	SKINTOP® DIX-M 20260 SI	M 20	0.236 in	2 pc.	Silicone	100
53316304	SKINTOP® DIX-M 25450 SI	M 25	0.197 in	3 pc.	Silicone	50
53316305	SKINTOP® DIX-M 25260 SI	M 25	0.236 in	2 pc.	Silicone	50
53316306	SKINTOP® DIX-M 25360 SI	M 25	0.236 in	3 pc.	Silicone	50
53316307	SKINTOP® DIX-M 25370 SI	M 25	0.276 in	3 pc.	Silicone	50
53316308	SKINTOP® DIX-M 32470 SI	M 32	0.276 in	4 pc.	Silicone	50
53316420	SKINTOP® DIX-M 16420	M 16	0.079 in	4 pc.	Acrylonitrile butadiene rubber	100
53320250	SKINTOP® DIX-M 20250	M 20	0.197 in	2 pc.	Acrylonitrile butadiene rubber	100
53320260	SKINTOP® DIX-M 20260	M 20	0.236 in	2 pc.	Acrylonitrile butadiene rubber	100
53320340	SKINTOP® DIX-M 20340	M 20	0.157 in	3 pc.	Acrylonitrile butadiene rubber	100
53320353	SKINTOP® DIX-M 20353	M 20	0.209 in	3 pc.	Acrylonitrile butadiene rubber	100
53320430	SKINTOP® DIX-M 20430	M 20	0.118 in	4 pc.	Acrylonitrile butadiene rubber	100
53320440	SKINTOP® DIX-M 20440	M 20	0.157 in	4 pc.	Acrylonitrile butadiene rubber	100
53320920	SKINTOP® DIX-M 20920	M 20	0.079 in	9 pc.	Acrylonitrile butadiene rubber	100
53325250	SKINTOP® DIX-M 25250	M 25	0.197 in	2 pc.	Acrylonitrile butadiene rubber	50
53325260	SKINTOP® DIX-M 25260	M 25	0.236 in	2 pc.	Acrylonitrile butadiene rubber	50
53325350	SKINTOP® DIX-M 25350	M 25	0.197 in	3 pc.	Acrylonitrile butadiene rubber	50
53325360	SKINTOP® DIX-M 25360	M 25	0.236 in	3 pc.	Acrylonitrile butadiene rubber	50
53325370	SKINTOP® DIX-M 25370	M 25	0.276 in	3 pc.	Acrylonitrile butadiene rubber	50
53325450	SKINTOP® DIX-M 25450	M 25	0.197 in	4 pc.	Acrylonitrile butadiene rubber	50
53325540	SKINTOP® DIX-M 25540	M 25	0.157 in	5 pc.	Acrylonitrile butadiene rubber	50
53325640	SKINTOP® DIX-M 25640	M 25	0.157 in	6 pc.	Acrylonitrile butadiene rubber	50
53332270	SKINTOP® DIX-M 32270	M 32	0.276 in	2 pc.	Acrylonitrile butadiene rubber	50
53332280	SKINTOP® DIX-M 32280	M 32	0.315 in	2 pc.	Acrylonitrile butadiene rubber	50

© (2026) Lapp Group - all rights reserved.

Article No.	Name	Thread size	Borehole diameter	Number of cable entries	Material	Delivery Unit
53332290	SKINTOP® DIX-M 32290	M 32	0.354 in	2 pc.	Acrylonitrile butadiene rubber	50
53332370	SKINTOP® DIX-M 32370	M 32	0.276 in	3 pc.	Acrylonitrile butadiene rubber	50
53332380	SKINTOP® DIX-M 32380	M 32	0.315 in	3 pc.	Acrylonitrile butadiene rubber	50
53332460	SKINTOP® DIX-M 32460	M 32	0.236 in	4 pc.	Acrylonitrile butadiene rubber	50
53332470	SKINTOP® DIX-M 32470	M 32	0.276 in	4 pc.	Acrylonitrile butadiene rubber	50
53332560	SKINTOP® DIX-M 32560	M 32	0.236 in	5 pc.	Acrylonitrile butadiene rubber	50
53332650	SKINTOP® DIX-M 32650	M 32	0.197 in	6 pc.	Acrylonitrile butadiene rubber	50
53332840	SKINTOP® DIX-M 32840	M 32	0.157 in	8 pc.	Acrylonitrile butadiene rubber	50
53332850	SKINTOP® DIX-M 32850	M 32	0.197 in	8 pc.	Acrylonitrile butadiene rubber	50
53332940	SKINTOP® DIX-M 32940	M 32	0.157 in	9 pc.	Acrylonitrile butadiene rubber	50
53340290	SKINTOP® DIX-M 40290	M 40	0.354 in	2 pc.	Acrylonitrile butadiene rubber	25
53340310	SKINTOP® DIX-M 40310	M 40	0.394 in	3 pc.	Acrylonitrile butadiene rubber	25
53340480	SKINTOP® DIX-M 40480	M 40	0.315 in	4 pc.	Acrylonitrile butadiene rubber	25
53340490	SKINTOP® DIX-M 40490	M 40	0.354 in	4 pc.	Acrylonitrile butadiene rubber	25
53340580	SKINTOP® DIX-M 40580	M 40	0.315 in	5 pc.	Acrylonitrile butadiene rubber	25
53340590	SKINTOP® DIX-M 40590	M 40	0.354 in	5 pc.	Acrylonitrile butadiene rubber	25
53340670	SKINTOP® DIX-M 40670	M 40	0.276 in	6 pc.	Acrylonitrile butadiene rubber	25
53340860	SKINTOP® DIX-M 40860	M 40	0.236 in	8 pc.	Acrylonitrile butadiene rubber	25
53340969	SKINTOP® DIX-M 40969	M 40	0.272 in	9 pc.	Acrylonitrile butadiene rubber	25
53350118	SKINTOP® DIX-M 50118	M 50	0.315 in	11 pc.	Acrylonitrile butadiene rubber	10
53350147	SKINTOP® DIX-M 50147	M 50	0.276 in	14 pc.	Acrylonitrile butadiene rubber	10
53350164	SKINTOP® DIX-M 50164	M 50	0.157 in	16 pc.	Acrylonitrile butadiene rubber	10
53350166	SKINTOP® DIX-M 50166	M 50	0.236 in	16 pc.	Acrylonitrile butadiene rubber	10
53350680	SKINTOP® DIX-M 50680	M 50	0.315 in	6 pc.	Acrylonitrile butadiene rubber	10
53350780	SKINTOP® DIX-M 50780	M 50	0.315 in	7 pc.	Acrylonitrile butadiene rubber	10
53350870	SKINTOP® DIX-M 50870	M 50	0.276 in	8 pc.	Acrylonitrile butadiene rubber	10

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.