SILVYN® KLICK M20X1.5/1 BK

Article No.: 55501045

Conduit connector; M 20; suitable for protective conduit size: 16; Polyamide; Halogenfree; UV-resistant; IP 68, IP 69;





Details

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	SILVYN®
Product type	Conduit connector
Delivery with lock nut	No
Including o-ring	No

© (2026) Lapp Group - all rights reserved.

Type of packaging	Bag
Delivery Unit	50
Mounting method	in threaded borehole with lock nut
Industry segment	Assembly Machines Energy Building Automation
customs code	3917400090

Electrical parameters

Product design

suitable for protective conduit size	16
With bending protection	No
Bending protection fixed installation	No
Flexibly installed bending protection	No
Conduit gland design	Straight
Divisible conduit gland	No
Rotatable thread	No
Total length	1.535 in
Overall width	0.984 in
Overall height	0.984 in
Clear width	0.472 in
Thread type	Metric
Thread size	M 20
Pitch of thread	1,5
Thread standard	DIN EN 60423
EMC shielding	No
Material sealing	Thermoplastic elastomers
Body material	Polyamide
Body material, short form	PA
Colour description	black
RAL color	RAL 9005

© (2026) Lapp Group - all rights reserved.

Product features

IP protection rating	IP 68 IP 69
Suitable for EX-applications	No
Flame-retardant	Yes
Flame retardance according to	UL 94 HB
UV-resistant	Yes
Chemical resistant	Yes
Halogenfree	Yes
Oil resistant	Yes
Impact proof	Yes
Vibration protection	Yes

Certifications and standards

CE marking	Yes
UL recognized	Yes
UL listed	No
cUR recognized	No
cUL listed	No
CSA certified	No
VDE certified	Yes
GGVS certified	Yes
DNV-certified	No

© (2026) Lapp Group - all rights reserved.

Ecolab certified	No
NSF certified	No
FDA certified	No
EHEDG certified	No

© (2026) Lapp Group - all rights reserved.

SILVYN® KLICK-M

Article No.	Name	Thread size	Colour description	suitable for protective conduit size	Delivery Unit
55500990	SILVYN® KLICK M63X1.5 GY	M 63	gray	54	10
55500995	SILVYN® KLICK M63X1.5 BK	M 63	black	54	10
55501000	SILVYN® KLICK M10X1.0 GY	M 10	gray	10	50
55501005	SILVYN® KLICK M10X1.0 BK	M 10	black	10	50
55501010	SILVYN® KLICK M12X1.5 GY	M 12	gray	13	50
55501015	SILVYN® KLICK M12X1.5 BK	M 12	black	13	50
55501020	SILVYN® KLICK M16X1.5/1 GY	M 16	gray	13	50
55501025	SILVYN® KLICK M16X1.5/1 BK	M 16	black	13	50
55501030	SILVYN® KLICK M16X1.5/2 GY	M 16	gray	16	50
55501035	SILVYN® KLICK M16X1.5/2 BK	M 16	black	16	50
55501040	SILVYN® KLICK M20X1.5/1 GY	M 20	gray	16	50
55501045	SILVYN® KLICK M20X1.5/1 BK	M 20	black	16	50
55501050	SILVYN® KLICK M20X1.5/2 GY	M 20	gray	21	50
55501055	SILVYN® KLICK M20X1.5/2 BK	M 20	black	21	50
55501060	SILVYN® KLICK M25X1.5/2 GY	M 25	gray	28	25
55501065	SILVYN® KLICK M25X1.5/2 BK	M 25	black	28	25
55501070	SILVYN® KLICK M32X1.5/3 GY	M 32	gray	34	25
55501075	SILVYN® KLICK M32X1.5/3 BK	M 32	black	34	25
55501080	SILVYN® KLICK M40X1.5/2 GY	M 40	gray	42	25
55501085	SILVYN® KLICK M40X1.5/2 BK	M 40	black	42	25
55501090	SILVYN® KLICK M50X1.5/2 GY	M 50	gray	54	10
55501095	SILVYN® KLICK M50X1.5/2 BK	M 50	black	54	10

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.