SILVYN® MPC M32 / 32 GY

Article No.: 55502447

Conduit connector; M 32; suitable for protective conduit size: 32; Polyamide; Halogenfree; IP 65, IP 67, IP 68 - 2 g/cm²;



Details

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	SILVYN®
Product type	Conduit connector
Delivery with lock nut	No
Including o-ring	No

© (2026) Lapp Group - all rights reserved.

Type of packaging	Bag
Delivery Unit	10
Mounting method	in threaded borehole
customs code	3917400090

Electrical parameters

Product design

suitable for protective conduit size	32
With bending protection	No
Bending protection fixed installation	No
Flexibly installed bending protection	No
Conduit gland design	Straight
Divisible conduit gland	No
Rotatable thread	No
Clear width	1,716.89 in
Thread type	Metric
Thread size	M 32
Pitch of thread	1,5
Thread length	0.63 in
Thread standard	DIN EN 60423
Wrench size 1	1.772 in
Hexagon corner dimensions	2.016 in
Wrench width	1.772 in
Lockable (two-part)	No
EMC shielding	No
Body material	Polyamide
Body material, short form	PA
Gland body material	Polyamide
Material fitting body shortname	PA
Colour description	gray
RAL color	RAL 7001

© (2026) Lapp Group - all rights reserved.

Product features

IP protection rating	IP 65 IP 67 IP 68 - 2 g/cm²
Suitable for EX-applications	No
Flame-retardant	No
UV-resistant	No
Chemical resistant	Yes
Acid-resistant	No
Halogenfree	Yes
Oil resistant	Yes
Impact proof	Yes
Strain relief	Yes

Certifications and standards

CE marking	Yes
UL recognized	Yes
UL listed	No
cUR recognized	No
cUL listed	No
CSA certified	No
VDE certified	No
Product standard according to IEC	IEC 61386-1 IEC 61386-23
GGVS certified	No
DNV-certified	No
Tested for fire protection for railway vehicles	No
Ecolab certified	No
NSF certified	No
FDA certified	No
EHEDG certified	No

© (2026) Lapp Group - all rights reserved.

SILVYN® MPC-M

Article No.	Name	Thread size	Colour description	suitable for protective conduit size	Delivery Unit
55502439	SILVYN® MPC M63 / 63 GY	M 63	gray	63	1
55502441	SILVYN® MPC M16 / 12 GY	M 16	gray	12	10
55502442	SILVYN® MPC M16 / 16 GY	M 16	gray	16	10
55502443	SILVYN® MPC M20 / 16 GY	M 20	gray	16	10
55502444	SILVYN® MPC M20 / 20 GY	M 20	gray	20	10
55502445	SILVYN® MPC M25 / 25 GY	M 25	gray	25	10
55502446	SILVYN® MPC M32 / 30 GY	M 32	gray	30	10
55502447	SILVYN® MPC M32 / 32 GY	M 32	gray	32	10
55502448	SILVYN® MPC M40 / 40 GY	M 40	gray	40	2
55502449	SILVYN® MPC M50 / 50 GY	M 50	gray	50	2
55502460	SILVYN® MPC M16 / 12 BK	M 16	black	12	10
55502461	SILVYN® MPC M16 / 16 BK	M 16	black	16	10
55502462	SILVYN® MPC M20 / 16 BK	M 20	black	16	10
55502463	SILVYN® MPC M20 / 20 BK	M 20	black	20	10
55502464	SILVYN® MPC M25 / 25 BK	M 25	black	25	10
55502465	SILVYN® MPC M32 / 30 BK	M 32	black	30	10
55502466	SILVYN® MPC M40 / 40 BK	M 40	black	40	2
55502467	SILVYN® MPC M50 / 50 BK	M 50	black	50	2
55502468	SILVYN® MPC M63 / 63 BK	M 63	black	63	1
55502469	SILVYN® MPC M32 / 32 BK	M 32	black	32	10

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.