SILVYN® KLICK PG 29 BK

Article No.: 61800915

Conduit connector; PG 29; Nominal size: 34.5; suitable for protective conduit size: 34; Halogenfree; UV-resistant; IP 68;





Details

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	SILVYN®
Product type	Conduit connector
Delivery with lock nut	No
Including o-ring	No

© (2026) Lapp Group - all rights reserved.

Type of packaging	Bag
Delivery Unit	25
Mounting method	in threaded borehole
customs code	3917400090

Electrical parameters

Product design

suitable for protective conduit size	34
With bending protection	No
Bending protection fixed installation	No
Flexibly installed bending protection	No
Total length	2.106 in
Overall width	1.732 in
Clear width	1.181 in
Nominal size	34.5 "
Thread type	PG
Thread size	PG 29
Pitch of thread	1,588
Thread length	0.571 in
Wrench width	1.575 in
EMC shielding	No
For conduit outer diameter	1.358 in
Gland body material	Polyamide
Material fitting body shortname	PA
Colour description	black

Product features

IP protection rating	IP 68
Suitable for EX-applications	No
Flame-retardant	Yes
Flame retardance according to	UL 94 HB

© (2026) Lapp Group - all rights reserved.

UV-resistant	Yes
Halogenfree	Yes
Oil resistant	Yes

Certifications and standards

CE marking	Yes
UL recognized	Yes
UL listed	No
cUR recognized	No
cUL listed	No
CSA certified	No
VDE certified	No
GGVS certified	No
DNV-certified	No
Ecolab certified	No
NSF certified	No
EHEDG certified	No

© (2026) Lapp Group - all rights reserved.

SILVYN® KLICK PG

Article No.	Name	Thread size	Colour description	suitable for protective conduit size	Delivery Unit
61800850	SILVYN® KLICK PG 13.5 GY	PG 13,5	gray	18	50
61800855	SILVYN® KLICK PG 13.5 BK	PG 13,5	black	18	50
61800860	SILVYN® KLICK PG 7 GY	PG 7	gray	10	50
61800865	SILVYN® KLICK PG 7 BK	PG 7	black	10	50
61800870	SILVYN® KLICK PG 9 GY	PG 9	gray	13	50
61800875	SILVYN® KLICK GP PG 9 BK	PG 9	black	13	50
61800880	SILVYN® KLICK PG 11 GY	PG 11	gray	16	50
61800885	SILVYN® KLICK PG 11 BK	PG 11	black	16	50
61800890	SILVYN® KLICK PG 16 GY	PG 16	gray	21	50
61800895	SILVYN® KLICK PG 16 BK	PG 16	black	21	50
61800900	SILVYN® KLICK PG 21 GY	PG 21	gray	28	25
61800905	SILVYN® KLICK PG 21 BK	PG 21	black	28	25
61800910	SILVYN® KLICK PG 29 GY	PG 29	gray	34	25
61800915	SILVYN® KLICK PG 29 BK	PG 29	black	34	25
61800920	SILVYN® KLICK PG 36 GY	PG 36	gray	42	25
61800925	SILVYN® KLICK PG 36 BK	PG 36	black	42	25
61800930	SILVYN® KLICK PG 48 GY	PG 48	gray	54	10
61800935	SILVYN® KLICK PG 48 BK	PG 48	black	54	10

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.