**1'' METAL NPT LOCKNUT**

**Article No.:** 811095

${ctx.productData.top5String}




CE




## Details

**Benefits**

- Item numbers ending with “LF” are lead-free product alternatives with otherwise identical product properties. “Lead-free” items do not include lead, which is currently permitted to account for up to four per cent in copper alloys, but could in future be banned in accordance with the RoHS directive.

**Application**

- For locking a SKINTOP® /SKINDICHT® cable gland on the inside of the application (e.g. housing).
- For thin-walled housings without a thread, which only allow one through-hole.

**Notes**

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

© (2026) Lapp Group - all rights reserved.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

**Remarks**

Locknut; stamped steel; 3/8" NPT - 2" NPT

## Technical Data

**General information**

| | |
|---|---|
| Brand | SKINDICHT® |
| Product type | Lock nut |
| Type of packaging | Bag |

**Electrical parameters**

**Product design**

| | |
|---|---|
| Glass-fibre reinforced | No |
| Thickness | 0.157 in |
| Thread type | NPT |
| Thread size | NPT 1" |
| Hexagon corner dimensions | 1.654 in |
| Wrench width | 1.496 in |
| EMC shielding | No |
| Body material | Steel |
| Colour description | metal |

**Product features**

| | |
|---|---|
| Suitable for EX-applications | No |
| Temperature (min.) | -60 °C |
| Temperature (max.) | 200 °C |
| Flame-retardant | Yes |
| UV-resistant | Yes |

© (2026) Lapp Group - all rights reserved.

| | |
|---|---|
| Halogenfree | Yes |
| Oil resistant | Yes |

**Certifications and standards**

| | |
|---|---|
| CE marking | Yes |
| UL recognized | No |
| UL listed | No |
| cUR recognized | No |
| cUL listed | No |
| CSA certified | No |
| VDE certified | No |
| GGVS certified | No |
| Ecolab certified | No |
| NSF certified | No |
| EHEDG certified | No |

© (2026) Lapp Group - all rights reserved.

## SKINDICHT® SM-NPT

| Article No. | Name | Thread size | Wrench width | Delivery Unit |
|---|---|---|---|---|
| 811092 | 3/8'' METAL NPT LOCKNUT | NPT 3/8" | | 100 |
| 811093 | 1/2'' METAL NPT LOCKNUT | NPT 1/2" | 1.063 in | 100 |
| 811095 | 1'' METAL NPT LOCKNUT | NPT 1" | 1.496 in | |
| 811096 | 1 1/4'' METAL NPT LOCKNUT | NPT 1 1/4" | 1.89 in | 50 |
| 811097 | 1 1/2'' METAL NPT LOCKNUT | NPT 1 1/2" | 2.165 in | 50 |
| 811098 | 2'' METAL NPT LOCKNUT | NPT 2" | 2.677 in | 25 |

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.