3/8in NYLON NPT LOCKNUT BLACK

Article No.: 911370

${ctx.productData.top5String}



Details

Benefits

- High stability thanks to fiber optic-reinforced polyamide.
- UL certification according to technical data enables the product to be used in North America (only valid in combination with a UL-approved SKINTOP® plastic cable gland).
- Self-extinguishing in accordance with UL94 V-2 (flammability test for plastics).
- The supporting surface facilitates easy installation with a wrench, and protects the housing against scratches.

Application

- For locking a SKINTOP® /SKINDICHT® cable gland on the inside of the application (e.g. housing).
- For thin-walled housings without a thread, which only allow one through-hole.
- Good oil and chemical resistance.
- Black variants are UV-resistant and therefore well suited for outdoor use.

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

© (2026) Lapp Group - all rights reserved.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	SKINTOP®
Product type	Lock nut
Type of packaging	Bag

Electrical parameters

Product design

Glass-fibre reinforced	Yes
Thickness	0.197 in
Thread type	NPT
Thread size	NPT 3/8"
Pitch of thread	1,41
Hexagon corner dimensions	0.953 in
Wrench width	0.866 in
EMC shielding	No
Body material	Polyamide
Body material, short form	PA
Colour description	black
RAL color	RAL 9005

Product features

Suitable for EX-applications	No
Temperature dynamic min.	-20 °C
Max. dynamic temperature	100 °C

© (2026) Lapp Group - all rights reserved.

Temperature static min.	-40 °C
Max. static temperature	100 °C
Temperature (min.)	-40 °C
Temperature (max.)	100 °C
Flame-retardant	Yes
Flame retardance according to	UL 94 HB
UV-resistant	Yes
Chemical resistant	Yes
Acid-resistant	No
Halogenfree	Yes
Oil resistant	Yes

Certifications and standards

CE marking	Yes
UL recognized	Yes
UL listed	No
cUR recognized	Yes
cUL listed	No
CSA certified	No
VDE certified	No
GGVS certified	No
Tested for fire protection for railway vehicles	No
Ecolab certified	No
NSF certified	No
FDA certified	No
EHEDG certified	No

© (2026) Lapp Group - all rights reserved.

SKINTOP® GMP-GL-NPT

Article No.	Name	Thread size	Wrench width	Colour description	Delivery Unit
911370	3/8in NYLON NPT LOCKNUT BLACK	NPT 3/8"	0.866 in	black	
911371	1/2in NYLON NPT LOCKNUT BLACK	NPT 1/2"	1.063 in	black	
911372	3/4in NYLON NPT LOCKNUT BLACK	NPT 3/4"	1.417 in	black	
911373	1in NYLON NPT LOCKNUT BLACK	NPT 1"	1.614 in	black	

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.