E-MO8/8SR screened-Modular-connector

Article No.: CE6326

${ctx.productData.top5String}



Details

Notes

Unless specified otherwise, the product values shown are rated values at room temperature. You can receive additional values, such as tolerances, upon request if they are available and have been released for publication.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

If applicable, the prices are solid metal prices without additional charges and VAT. Sales only to business customers.

Remarks

Technical Data

General information

Brand	EPIC®
Product type	Data connectors
Delivery Unit	10
customs code	8536904000

© (2026) Lapp Group - all rights reserved.

Electrical parameters

Rated voltage	125 V DC according to (manufacturer specifications)
Rated current	1.5 A according to (manufacturer specifications)

Product design

Shielded	Yes
Number of contacts	8
Locking mechanism	Latch
Dust protection cap	No
Type of housing	Rectangular housing
Connector housing design	Straight
Coded	No
With thread	No
Format of connector	RJ45
Connector type	Plug
Screen contact	Yes
Contact connection type	Insulation displacement connector
Type of connection	Plug to socket
Reusable	No
Assembly type	Field Configurable
Connection type conductor	Insulation displacement connector
Shield contact type	Crimp termination
Connectable conductor cross section solid-core min. (AWG)	26 AWG
Connectable conductor cross section solid-core max. (AWG)	24 AWG
Connectable conductor cross section stranded min. (AWG)	26 AWG
Max. connectable fine-wire conductor cross-section (AWG)	24 AWG
Material contact	Copper alloy
Contact material, short form	CuSn

© (2026) Lapp Group - all rights reserved.

Contact coating material	Gold-plated
Contact coating material, short form	Au

Product features

Min. number of insertion cycles	100
Pollution degree	3
Installation temperature min.	-20 °C
Max. assembly temperature	85 °C
Operating temperature min.	-20 °C
Operating temperature max.	85 °C
UV-resistant	No
Contact type application	Data / Signals
Strain relief	No

Certifications and standards

CE marking	No
EAC certified	Not required
EAC certification number	Отказное письмо № 481
UL recognized	No
UL listed	No
cUR recognized	No
cUL listed	No

© (2026) Lapp Group - all rights reserved.

E-MO8/8SR shielded-modular-connector

Article No.	Name	Number of contacts	Delivery Unit
CE6326	E-MO8/8SR screened-Modular-connector	8	10

© (2026) Lapp Group - all rights reserved.

V1.1

© (2026) Lapp Group - all rights reserved.